

Mobile gas source escape system 移动供气源逃生系统

- 不锈钢小推车：
不锈钢车架增强防腐性，可配置刹车装置。中压导管：主导管长度30米，两个分支导管长度各10米，中压导管总长度可根据需求延长至90米。

- 4只6.8升碳纤维瓶、减压阀、2只供气阀和2只全面罩等部件组成。有5升、6升钢瓶、9升碳纤维可选。

特点：

可同时供两人使用，确保长时间工作。可及时更换气源，不影响工作，有效节省时间。

产品技术参数：

| | | | |
|--------------------------|---------|--------|------------|
| 气瓶水容积 | 6.8L | 报警压力 | 5.5±0.5Mpa |
| 气瓶工作压力 | 30Mpa | 报警发声声级 | 90dB |
| 吸气阻力 | ≤500pa | 气瓶数量 | 4只 |
| 呼气阻力 | ≤1000pa | | |
| 中压导管长度：标准50M，可根据具体需求增加长度 | | | |

Products Specifications:

| | | |
|------------------------|-----------------------|---------|
| Cylinder Quantity | 4 | 2 |
| Material | Carbon fiber cylinder | |
| Volume | 4*6.8L | 2*6.8L |
| Rated Working Pressure | 300bars | |
| Rated Service Time | 240mins | 120mins |
| ReducerInput Pressure | ≤ 300bars | |
| Output Pressure | About 7.5 bars | |
| Maximum Output Flow | ≥1000L/min | |

Trolley breathing apparatus is especially used in tunnel, pipe or other limited space, and other contaminated environment for a long time difficult and complicated work. Composed of stainless steel trolley, carbon fiber cylinder, air supply tube, reducer, demand valve and full face mask etc.

Optional 6.8L, 9L carbon cylinder or 5L, 6L steel cylinder Optional 2 or 4 cylinder device. Optional horizontal or vertical cylinder placement.

